

## Door Leaf Safety Sensors

(p/n 10294, 10295, 11379)



The door leaf mounted safety sensors are failsafe active infrared sensors which function by measuring the distance to any obstacle. They are used on automatic swing doors to prevent doors coming into contact with the users.

### ▲ High Level of Safety

With a maximum detection area of 40cm wide in front of the door leaf at 2 metres high, the sensors can easily detect obstacles across the entire width of the door leaf, and they can be easily installed on both the push and pull side of the door leaf, and the three dimensional protection area makes it particularly suitable for protecting people with disabilities.

### ▲ Expandable

The units can easily be daisy chained across up to 6 modules to cover the entire door width, regardless of the width of the door in question. Each module recognises

when it is part of a daisy-chain and it automatically adjusts its settings accordingly. The advanced design of the hardware and software allows the sensor to easily adapt to all floor types, even ones with high-contrast which would trick other sensors into thinking that an obstacle is present. Examples of this would include highly reflective surfaces such as stainless steel plate, metal grids, water puddles, wet floors, washed vinyl, snow-covered ground, etc.

### ▲ Ease of Maintenance

Pressing the built in push button once is enough to adjust the sensor for the standard installation heights, and more advanced fine tuning is possible by using the integrated DIP-switches located under the cover. The safety sensor is available in a number of different lengths, including a 350mm long model, usually used on the face opposite the motor, and a 1200mm long model which can be cut down to fit the motor side of the door, among other sizes.

# Safety Devices



## Specifications:

Supply Voltage:	12-24Vac +/- 10%
	12-30Vdc -5%/+10%
Reaction Time:	64ms (typical)
Number of beams:	4
Technology:	Active Infrared with background suppression
Mounting Height:	1.1m to 3m (according to floor reflectivity)
Dimensions:	43.5mm H x 47.5mm D x Length
Material:	ABS Lens Aluminium Powdercoated Body (Black)
Ingress Protection:	IP53

Temperature Range: - 25° to + 55° C

Cable Routing to Automation: Typically via pvc flexible conduit



## Options Available

P/N: 11379: 350mm long unit

P/N: 10295: 700mm long unit

P/N: 10294: 900mm long unit